

aluminium dent repair

The Eurotec Aluminium Dent Repair System features the following:

- **Capacitor Discharge.**
The aluminium spotter incorporates a specialised design that uses capacitor discharge to maintain a higher power that is required for welding aluminium.
- **Digital Amp Readout.**
Aluminium requires a different approach when repairing body panels, and adjusting the current output on the Spotter, can now be done with a great deal of accuracy, via the digital amp readout.
- **Multi Function Pulling Bar**
The fixed and pivoted bases are equipped with suction cups that allow their positioning both horizontally and vertically. Made completely of aluminium, meaning its strong and reliable, but lightweight and easy to use.
- **All the accessories you need:**
 - Aluminium spotter
 - Hand operated puller
 - Set of 7 specialized hammers
 - Multi Function Pulling bar & attachments
 - Specialist shaped wedges kit
 - Complete set of consumables



ALUSPOTTER 1500 TECHNICAL SPECIFICATIONS

Supply Voltage	230V Single Phase 50-60Hz
Nominal Current	5 A
Nominal Power	1000 VA
Capacity	66 mF
Dimensions (Aluspotter only)	320mm L x 197mm W x 249mm H
Net Weight (Aluspotter only)	14 kg
Gross Weight with Accessories (Aluspotter only)	21 kg



*the aluminium dent system
the professionals use*

4/21 Duntroon St Brendale Q 4500 p: 07 3881 5000 f: 07 3881 5050
e: enquiries@eurotec.net.au w: www.eurotec.net.au